

MILKOR STOPPER

STOPPER CONVERTIBLE



This weapon is a quick-reload, single-shot enforcer. The stopper convertible can be used to control riots and can also be utilised in lethal situations by various entities, such as law enforcement, military and tactical personnel. It is configurable with either a 40 mm or a 37/38 mm barrel.



CALIBRE & ROUNDS

40 mm Low-Velocity (LV)
40 mm Less-Lethal
37/38 Less-Lethal



PRACTICAL FIRING RATE

Capable of firing 12 rounds
per minute (operator dependant)



EFFECTIVE RANGES

400m Low-Velocity
ammunition standard



TECHNICAL SPECIFICATIONS

Calibre & Rounds	40 mm Low-Velocity (LV) 40 mm Less-Lethal 37/38 Less-Lethal
Type	Single round light weight break-open weapon
Capacity	1 Round
Firing Method	Double action
Practical Firing Rate	Capable of firing 12 rounds per minute (Operator dependant)
Barrel Type	6 Constant 1 turn in 1200 mm (1:47.24")
Overall length (Butt retracted/extended)	642 mm/720 mm with compensator 608 mm/686 mm without compensator
Weight (Empty)	2.41 kg
Effective Range	400 m (Low-Velocity ammunition standard)
Accessory Rail	STANAG 4694 NATO Accessory Rail (NAR) and 2 side mounted 44 mm picatinny rails
Standard Sight	Several options are available as per customer request
Height	162 mm
Width	69 mm

